SELF RESCUE

ASSISTED RESCUE

MULTI-PERSON EVACUATION



Escape and rescue certified to a higher standard.

DEUS® 3700 Controlled Descent Device for Industrial Escape & Rescue

just two fingers.

Whether you work on 10 foot high platforms or 500 foot towers, the DEUS 3700 is a safe, easy-to-use and reliable tool for escape, self-rescue, assisted-rescue, travel restraint and more. Third-party tested and certified to the ANSI Z359.4-2007 fall protection rescue standard, the 3700 helps employers meet the OSHA requirement for prompt rescue while reducing the risk of suspension trauma for the worker. It works in both directions so multiple people can descend one-afteranother, and ropes can be replaced so it's cost-effective and versatile. The 3700 features quadruple-redundant braking, automatic speed-limiting technology, hands-free descent, and a speed control dial to control descent with

actual

SAFEST RESCUE: Redundant Brake Technology

CERTIFIED: ANSI Z359.4-2007 and NFPA 1983-2006 "E"

HANDS FREE DESCENT: Stop-Go-Speed Control with 2 Fingers









One compact, lightweight device for escape, self-rescue or assisted rescue.

Hands Free

Operates fully hands free, stop or go, while protecting you from free fall.

Extra, Extra, Extra, Extra Safe

Four independent brakes provide extra safety, versatility and control: an always-active centrifugal brake, a control knobactivated drum brake, a hands-free self-adjusting figure-8, and a manual rope-tailing brake for precise control.

Simple Operation

The oversized control knob is all you need for complete control, even with heavy gloves. Stop or go and change speed any time during descent.

Lightweight & Portable

Pocket-sized and just 2.4 lb (1.1 kg) (plus rope).

Cost-Saving Versatility

Use the same 3700 for work at different heights. Simply replace the rope in seconds.





Proven Reliable

Third-party certified to meet ANSI Z359.4-2007 requirements. Surpasses the NFPA 1983-2006 standards.

Your All-in-One Rescue System

Use the DEUS 3700 for selfrescue, assisted rescue and multiple person evacuation situations. Pick-offs and confined space can also be performed with additional training.

Built for Performance

Features a rock-solid case and professional grade construction.

Uses DEUS Rope

The 3700 is designed to be used only with the specific DEUS rope: 7.5 mm,

fire-, cut-, abrasion-, chemical-, and UV resistant. This rope is 50% stronger than the ANSI minimum requirements.

Only from DEUS Rescue

DEUS Rescue delivers innovative professional rescue solutions worldwide. For more information, visit www.DEUSrescue.com.



Available as part of complete kits for escape and rescue

SPECIFICATIONS

Model No.: DEUS 3700

Item: Controlled Descent

Device

Weight: 2.4 lb (1.1 kg) (plus rope)

Dimensions: 5.3 x 3.8 x 2.2 in

 $(13 \times 10 \times 6 \text{ cm})$

Descent Rate: 6.6 ft/sec max

Load Rating: Up to 310 lb (140 kg)

Operation: Hands-free or manual

Construction: Aluminum, stainless steel,

titanium and brass

Standards: ANSI Z359.4-2007,

NFPA 1983 (06 ED) "E" and

meets OSHA

Available 3700 Kits:

Industrial Escape Kit

Industrial Escape &

Rescue Kit

Other kits and accessories also available

